

ERVIN STAINLESS

The world standard for quality

The Ervin stainless technology is the most advanced in the world, combining the unique resources of the Tecumseh, Michigan, R&D center, and the expertise of the German facility in Sprockhövel. This makes Amachrome the highest quality ferritic stainless abrasive media.

Each grain is individually processed and sorted to ensure the right spherical shape and resilience to provide the longest durability.

Amachrome is used in most impact treatments:

- Cleaning and deburring,
- Surface enhancement and finishing,

Amachrome is recommended where ferrous contamination should be avoided:

- Aluminum profiles prior to coating, castings and other parts,
- Stainless steel forgings, structural parts and welded fabrications,
- Zinc, Brass and other non ferrous metals die-castings and parts,
- Granite, other natural stone and concrete to create an anti-skidding roughness finishing.

AMACHROME

BENEFITS:

- Environmentally friendly, from manufacturing process to blasting and recycling,
- Technically effective with the highest energy transmission and a long durability,
- Economically sound providing the lowest operating cost,
- Amachrome is contaminant free, thanks to its confined process of production.







Amachrome at work: enhancing and securing your operation!



APPARENT DENSITY
4,3 kg/dm³
HARDNESS
New: 270 HV Conditioned: 370 HV (Conditioning takes place during normal use.)
PACKAGING
500 kg Euro-pallets, 20 PE-bags x 25 kg, cardboard box, plastic cover shrink wrapped

CHEMICAL ANALYSIS							
Carbon~0.17%							
Silicon~1.8%							
Manganese ~1.2%							
Chromium~18%							

AMACHROME SCREENING																		
SPECS.	3,5	3,0	2,5	2,0	1,7	1,4	1,25	1,0	0,8	0,7	0,6	0,5	0,4	0,3	0,2	0,14	0,09	<0,09
300		5% MAX			90% MIN													
200				5% MAX		90% MIN												
150					5% MAX		90% MIN											
100						5% MAX		90% MIN										
60							5% MAX			90% MIN								
50								5% MAX			90% MIN							
40									5% MAX				90% MIN					
30												5% MAX				90% MIN		
20														5% MAX			90% MIN	
10															5% MAX			

For product optimisation we reserve the right to change specifications *Special sizes are available upon request



Ervin Germany GmbH

Auf dem Bruch 11, D-45549 Sprockhövel Germany

Phone: + 49 (0) 23 24 90 22 244 Fax: + 49 (0) 23 24 59 77 88 Email: sales@ervin-germany.com